No.: GJW2021-0722

Page 1 of 9 Pages

Safety Data Sheets (SDSs)

Product Name:	Rechargeable Prismatic Lithium-ion Cell		
Commissioner:	Ruipu Energy Co., Ltd.		

Vkan Certification & Testing Co., Ltd.

Ref, No.: GJW2021-0722 Page 2 of 9 Pages

Rei, No.: GJW2021-0722 Page 2 01 9 Pages			
Name of Product	Rechargeable Prismatic Lithium-ion Cell		
Type/Mode	CB71173204EB 3.2V 280Ah 896Wh		
Commissioned by	Ruipu Energy Co., Ltd.		
Commissioner address	No.205, Binhai 6th Road, Konggang New District, Longwan District, Wenzhou, Zhejiang, China.		
Supplier	Ruipu Energy Co., Ltd.		
Supplieraddress	No.205, Binhai 6th Road, Konggang New District, Longwan District, Wenzhou, Zhejiang, China.		
Inspection according to	Globally Harmonized System of Classification and Labelling of Chemicals (GHS, Rev.8)		
Emergency telephone number	+86-18301870986/+86-021-38618067		
Remarks			
Seal of CVC			
Date of issue: 2021.3.9			

Approved by: Huang Kun Reviewed by: Zhang Siyao Tested by: Liu Zhen

duengen Zhang siyon trochm

Ref, No.: GJW2021-0722 Page 3 of 9 Pages

SECTION 1:PRODUCTANDCOMPANY IDENTIFICATION

Product Identifier

Product name: Rechargeable Prismatic Lithium-ion Cell Model: CB71173204EB 3.2V 280Ah 896Wh

Other means of identification

Synonyms: none

Relevant identifieduse of Product and uses advised against

Recommended Use:-Uses advised against:

Details of the Supplier of the safety data sheet:

Name: Ruipu Energy Co., Ltd.

Address: No.205, Binhai 6th Road, Konggang New District, Longwan District,

Wenzhou, Zhejiang, China.

Telephone: +86-18301870986/+86-021-38618067

Fax: -Postcode: -

E-mail address: gaos@chinarept.com

Emergency telephone number

Company Emergency Phone Number: +86-18301870986/+86-021-38618067

SECTION 2:HAZARDS IDENTIFICATION

Classification

The watt-hour rate of the product is 896 Wh, it is belong to class 9 dangerous goods.

The product is tested according to Section 38.3 of the Recommendations on the Transport of Dangerous Goods, the test report number: RZUN2021-0923

Other information

Caution! Avoid short circle, place in high temperature environment, put into water, or damage the shell.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization: Mixtures

Description:Chemical power supply based on nonaqueous electrolyte. Composed by positive electrode, negative electrode, diaphragm, electrolyte and shell.

Hazardous ingredients:

Common	Chemical	Concentration	CAS No.	EC No.
Chemical Name	Formula	(%)	CAS NO.	EC NO.
Aluminum	Al	12.4	7429-90-5	213-0072-3

Ref, No.: GJW2021-0722 Page 4 of 9 Pages

Copper	Cu	16.1	7440-50-8	213-159-6
Lithium Iron	LiFePO₄	30	15365-14-7	921-62-3
Phosphate	En ci O ₄	30	10000 14 7	321 02 3
Carbon	С	13.5	7782-42-5	231-955-3
(proprietary)	C	15.5	1102-42-3	231-900-3
Separator	(C ₃ H ₆) _n	2.0	9003-07-0	,
(proprietary)		3.9	9003-07-0	/
Electrolyte	LiPF ₆ /EC+DE	24.1	1	1
(proprietary)	С	24.1	/	/
Lead	Pb	Not Detected	7439-92-1	231-099-0
Cadmium	Cd	Not Detected	7440-43-9	231-152-8
Mercury	Hg	Not Detected	7439-97-6	18540-29-9

SECTION 4: FIRST-AID MEASURES

First aid measures

Eye Contact: Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact: Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation: Move to fresh air. If symptoms persist, call a physician.

Ingestion: Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Swallowing: Do not induce vomiting. Get medical attention.

Most Important Symptoms/Effects

No information available.

Indication of any immediate medical attention and special treatment needed

Inform physician. Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

CO₂, dry chemical powder, wet sand, plenty of water (for cooling).

Unsuitable Extinguishing Media:No information available.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

Special hazards arising from the substance or mixture:

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when

Ref, No.: GJW2021-0722 Page 5 of 9 Pages subjected to high temperature (>150°C), When damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

SECTION 6:ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

Environmental precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non-combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

SECTION 7:HANDLING AND STORAGE

Precautions for safe handling

Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Avoid mechanical or electrical abuse.

More than a momentary short circuit will generally reduce the battery service life. Avoid reversing battery polarity within the battery assembly. In case of a battery unintentionally be crushed, rubber gloves must be used to handle all battery components. Avoid contact with eyes, skin. Avoid inhalation. No smoking at working site. Materials to Avoid: Strong oxidizing agents, Corrosives.

Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated area. Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short-circuits. Materials to Avoid: Strong oxidizing agents, Corrosives.

SECTION 8:EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls:

Use ventilation equipment if available. Safety shower and eye bath.

Personal Protective Equipment:

Ref, No.: GJW2021-0722 Page 6 of 9 Pages

Respiratory System: Not necessary under conditions of normal use.

Eyes: Not necessary under conditions of normal use.

Clothing: Wear appropriate protective clothing.

Hand: Safety gloves.

Other Protect:

No smoking, drinking and eating at working site. Wash thoroughly after handling.

SECTION 9: Physical and chemical properties

	Form: Prismatic			
PhysicalState	Color: Blue			
	Odour: Odourless			
	Odor Threshold: No information available			
Change in condition:				
pH, with indication of the concentration		Not determined.		
Melting point/freezing point		Not determined.		
Initial boiling point and Boiling range:		Not determined.		
Flash Point		Not determined.		
Flammability (solid, gas)		Not determined.		
Upper/lower flammability or explosive limits		Not determined.		
Auto-ignition temperature		Product is not self-igniting.		
Decomposition temperature		Not determined.		
Other Information		No further relevant information available.		

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Stable under recommended storage and handling conditions (see section 7).

<u>Chemical stability:</u> Stable under normal conditions of use, storage and transport.

Thermal decomposition/conditions to be avoided: No decomposition if used according to specifications.

<u>Possibility of Hazardous Reactions:</u> None under normal processing.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to avoid: Strong heating, fire, Incompatible materials.

Incompatible materials: Strong oxidizing agents. Strong acids. Strong bases.

<u>Hazardous Decomposition Products:</u> Carbon oxides, other irritating and toxic gases.

Ref, No.: GJW2021-0722 Page 7 of 9 Pages

SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity: No data available.

Skin corrosion/irritation: No irritant effect.

<u>Serious eye damage/irritation:</u> Cause serious eye irritation.

<u>Respiratory or skin sensitization:</u> No sensitizing effects known.

<u>Specific target organ system toxicity:</u> No information available.

Note: The internal battery materials may cause irritation to eyes and skin.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity: No further relevant information available.

<u>Persistence and degradability:</u>No further relevant information available.

<u>Bioaccumulative potential:</u> No further relevant information available.

Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment:

PBT: Not applicable. vPvB: Not applicable.

Other adverse effects: No information available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation: Lithium batteries are best disposed of as a non-hazardous waste when fully or mostly discharged. Contact a licensed professional waste disposal service to dispose of large quantities materials.

Other disposal recommendations

Recommendation: Disposal must be made according to official regulations.

SECTION 14: TRANSPORT INFORMATION

The product had been tested according to the requirements of the UN manual of tests and Criteria, Part III, subsection 38.3.(see section 2)

EmS No: F-A,S-I Marine pollutant: No

Environmental hazards: Not applicable.

Special precautions for user: Not applicable.

Hazard Class: Class 9 UN/ID Number: UN3480 Packaging Group: II

Air transport

Ref, No.: GJW2021-0722 Page 8 of 9 Pages

Label for conveyance: Class 9 lithium battery hazard label, Cargo Aircraft Only Label

The lithium ion batteries package complied with the requirements of Section IA of Packing Instruction 965 of 62nd DGR Manual of IATA (2021 edition).

Maritime transport

Label for conveyance: Class 9 lithium battery hazard label

The lithium ion batteries package complied with the requirements of Packing Instruction P903 of

IMDG CODE (Amdt. 39-18) (2018 Edition)

Land transport

Label for conveyance: Class 9 lithium battery hazard label

The lithium ion batteries package complied with the requirements of Packing Instruction P903 of European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR 2021)

SECTION 15: REGULATORY INFORMATION

International Regulation:

Globally Harmonized System of Classification and Labeling of Chemicals

Recommendations on the Transport of Dangerous Goods Model Regulations

IATA Dangerous Goods Regulations (DGR)

International Maritime Dangerous Goods (IMDG CODE)

EU Regulation:

EU regulation (EC) 1272/2008 on "Classification, Labeling and Packaging of Substances and Mixtures" (CLP)

 $\label{eq:Registration} \textbf{Registration, Evaluation and Authorization of Chemicals} \ \ (\textbf{REACH})$

European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)

US Regulation:

American National Standard for Hazardous Workplace Chemicals – Hazard Evaluation and Safety Data Sheet and Precautionary Labeling Preparation

SECTION 16: OTHER INFORMATION

This file is only effective to the batteries (CB71173204EB) provided by commissioner Ruipu Energy Co., Ltd.. The commissioner provides the composition information of batteries, and promises its integrity and accuracy. Users should read this file carefully, and use the batteries in correct method. Vkan Certification & Testing Co., Ltd. (CVC) doesn't assume responsibility for any damage or loss because of misuse of batteries.

Ref, No.: GJW2021-0722 Page 9 of 9 Pages

Important

- **1.** The test report is invalid without the official stamp of CVC.
- 2. Nobody is allowed to photocopy or partly photocopy this test report without written permission of CVC.
- The test report is invalid without the signatures of Ratifier, Reviewer and Testing engineer.
- **4.** The test report is invalid if altered,
- Objections to the test report must be submitted to CVC within 15 days,
- **6.** This report is valid for the samples provided by commissioner only.

*The test data and test results given in this test report should only be used for purposes of scientific research, teaching and internal quality control when the CMA symbol is not presented. *

Address: No.3, Tiantai 1st Road, Kaitai Avenue, Science City, Guangzhou,

Guangdong, China.

Building D, BASIGO INTELLIGENT, No.179, Guangpu East Road,

Huangpu District, Guangzhou, P. R. China.

Tel: 020 32293888 FAX: 020 32293889 Post Code: 510663

E-mail: office@cvc.org.cn

http://www.cvc.org.cn